



PRODUCT FEATURES

- Step-dimming 100% 50% 20% control over ON/OFF switch with memory function
- Ultra Slim design, profile less than 23mm
- Excellent and uniform lighting performance thanks to side-lit light guide technology
- Easy installation featured with twist-and-lock
- Tool-less wiring connection design
- IP54 version available for moisture application



APPLICATIONS

- Bedrooms
- Dining Rooms
- Residential

PRODUCT INFORMATION

Model Number	FCL73300v1-mt/wf/tw
Product Code	FCL73300v1-mt/wf/tw
MM Code	-

ELECTRICAL INFORMATION

Input Voltage	220-240 VAC
Frequency	50/60 Hz
Input Current	150 mA
Power	15 W
Power Factor	0.5

DIMMING AND CONTROLS

Dimmability	Yes
Protocol	Matter over Wi-Fi

PHOTOMETRICAL INFORMATION

Luminous Flux	2300
Luminous Efficacy	113 lm/W
Colour Temp	2700-6500 K
CRI	Ra80
Beam Angle	120 °
Colour Consistency	6

LIFE PERFORMANCE

Lifetime	25,000hrs L70B50@Ta25°C
Number of Switching Cycles	100000

STANDARDS AND APPLICATION

IP	IP20/IP20
IK	02
Protection Class	CL II
Glow Wire	650 °C
Photobiological Safety Group	RG0
Standards Compliance	IEC/EN60598-1, IEC/EN60598-2-1

INSTALLATION AND CAPABILITIES

Installation	Surface Mount
--------------	---------------

MECHANICAL AND MATERIAL

Optics Material	PC
Housing Material	PP
Housing Colour	White
Diameter	Ø294 mm
Height	23 mm
Weights	565 g

LOGISTIC INFORMATION

MM Code	Packaging Unit	Outer Box Dimensions			Gross Weight per Outer Box
		L	W	H	
	pcs/unit	mm	mm	mm	kg

-