Airam Led 4W 15000h BX

Dimmable range for all residential lighting needs

A lamp series covering all residential lighting needs. All models are dimmable with an LED dimmer. The clear DIM symbol indicates dimmability. The lamps have a pleasant warm white (2700 K) colour temperature. The opal light source provides nonglaring light. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented. Ensure the compatibility of the range's 12V lamps with your transformer.

Clear dimmable R63 reflector LED lamp 4W 2700K E27 345lm 36D 15000h 63x102mm, cardboard packing. Supply frequency ~50/60Hz.

4W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714127	A7LEF3	0.09	Airam Led





4W 15000h BX

EC001959

Mounting	
Degree of protection (IP)	IP20
Structure	
Colour	Transparent
Housing colour	Colourless
-	
Dimming and control	
Dimming phase cut-on	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
	110
Photometric data	
Luminous flux (min) (lm)	345
Luminous flux (max) (lm)	345
Luminous intensity (cd)	570
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700
Colour temperature (max) (K)	2700
Beam angle (min)	36
	36
Beam angle (max)	SDCM6
Colour consistency (McAdam ellipse)	RG1
Photobiological safety according to EN 62471	RUI
Lifetime and encoder	
Lifetime and capacity	
M	
Measurements	(0
Diameter (mm)	63
Length (mm)	102
Electrotechnical data	
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	20
Nominal current (max) (mA)	24
Power factor	0.8
Voltage type	AC

