

IP44

-O
3 x 2,5

IP44 E27 GLC BK

Wall luminaire

The Käpylä luminaires are timeless classics for Nordic yards. Choose the body in a colour that matches your house: steel, white or black. The glass dome protects the bulb and lets the light shine freely both upwards and downwards through the body's steel rings. Bulb choice has a significant impact on mood and luminosity. Use the Käpylä Mini together with Käpylä bollards to create a unified look.

Käpylä Outdoors wall luminaire No dim; IP44; IK02; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour bk; Cover Glass transparent



IP44 E27 GLC BK

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107606	A1UAAA	1.164	Käpylä

Mounting	
Degree of protection (IP)	IP44
Suitable for ceiling mounting	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Suitable for emergency lighting	No
Fit for monitor workplace	No
Suitable for wall mounting	Yes
Connection type	Screwed terminal
Suitable for suspended mounting	No
Suitable for light line configuration	No
Number of poles	3
Conductor cross section (mm ²)	2.5
Type of wiring	Ending

Structure	
With lamp	No
Material housing	Stainless steel
Material cover	Glass transparent
Lamp type	LED exchangeable
Suitable for number of lamps	1
Lamp holder	E27
Type of grid	None
With air slots	No
Control gear included	No
Highest energy efficiency class of the exchangeable	A++
Lowest energy efficiency class of the exchangeable	A
Housing surface protection	Powder coating
Emergency power supply integrated	No

Dimming and control	
With movement sensor	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI-2	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming GPRS	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Dimming depending on control gear	No
Dimming DSI	No
Bluetooth operated	No

Photometric data	
Beam angle	Open beam
Light outlet	Direct/indirect
Light sharing	Symmetric
Light distributor	Other
Colour temperature switchable	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) [°C]	-20
Rated ambient temperature acc. IEC62722-2-1 (max) [°C]	25

Measurements	
Outer diameter (mm)	221
Length (mm)	221
Width (mm)	221
Height/depth (mm)	243

Electrotechnical data	
Type of control gear	Not required
Nominal voltage (min) (V)	230
Voltage type	AC
Protection class	I
Suitable for lamp power (min) (W)	1
Nominal voltage (max) (V)	230
Suitable for lamp power (max) (W)	11