

IP44


-O
3 x 2,5

PARK W IP44 E27 MAX 60W GR

Wall luminaire

The clean-lined and stylish Park garden luminaires blend in with modern residential architecture. The steel rings inside the diffuser prevent glare and bring the modern design to life. Combine these models with Park Bollard luminaires to create a harmonious and stylish lighting solution for your outdoor spaces. You can change the atmosphere and level of illumination through the choice of lamp.

Park Outdoors wall luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour gr; Cover Plastic, transparent



PARK W IP44 E27 MAX 60W GR

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4116103	A1PUBA	0.844	Park

Mounting	
Degree of protection (IP)	IP44
Suitable for ceiling mounting	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Suitable for emergency lighting	No
Fit for monitor workplace	No
Suitable for wall mounting	Yes
Connection type	Screwed terminal
Suitable for suspended mounting	No
Suitable for light line configuration	No
Number of poles	3
Conductor cross section (mm ²)	2.5
Type of wiring	Ending

Structure	
With lamp	No
Material housing	Stainless steel
Material cover	Plastic, transparent
Lamp type	LED exchangeable
Suitable for number of lamps	1
Lamp holder	E27
Type of grid	Other
With air slots	No
Control gear included	No
Highest energy efficiency class of the exchangeable	A++
Lowest energy efficiency class of the exchangeable	A
Housing surface protection	Powder coating
Emergency power supply integrated	No

Dimming and control	
With movement sensor	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI-2	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming GPRS	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Dimming depending on control gear	No
Dimming DSI	No
Bluetooth operated	No

Photometric data	
Light outlet	Direct
Light sharing	Symmetric
Light distributor	Reflector
Colour temperature switchable	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) [°C]	-20
Rated ambient temperature acc. IEC62722-2-1 (max) [°C]	25

Measurements	
Outer diameter (mm)	100
Length (mm)	115
Width (mm)	150
Height/depth (mm)	300

Electrotechnical data	
Type of control gear	Not required
Nominal voltage (min) [V]	230
Voltage type	AC
Protection class	I
Suitable for lamp power (min) [W]	1
Nominal voltage (max) [V]	230
Suitable for lamp power (max) [W]	10.5