



-O
3 x 2,5

IP44




IP44 13W/830 PCC ANT H1000


Flen Bollard Outdoor luminaire 13W 3000K 1100lm
IP44; Protection cl. I; L70B50 30000h; LED not
exchangeable; CRI>80; Ending; 3x2.5mm²; Housing al;
Colour ant; Cover Plastic, transparent

IP44 13W/830 PCC ANT H1000


PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4126253	A1FLEC	3.01	Flen Bollard



4126251



4126252



Mounting	
Degree of protection (IP)	IP44
Connection type	Other
Type of luminaire	Bollard luminaire
Number of poles	3
Conductor cross section (mm ²)	2.5
Type of wiring	Ending
Structure	
With lamp	Yes
Colour housing	Anthracite
Material housing	Aluminium
Material cover	Plastic, transparent
Lamp type	LED not exchangeable
Suitable for number of lamps	1
Lamp holder	Other
Control gear included	No
With base plate	Yes
Energy efficiency class of the built-in lamp	A++, A+, A (LED) Other
Dimming and control	
With movement sensor	No
With light sensor	No
Photometric data	
Effective luminous flux (lm)	1100
Colour temperature (min) (K)	3000
Colour rendering index CRI	80-89
Colour of light (alphanumeric)	White
Colour temperature (max) (K)	3000
Light distributor	None
Light outlet	Direct
Light sharing	Symmetric
Beam angle	Open beam
Colour temperature switchable	No
Lifetime and capacity	
Rated life time L70/B50 at 25 °C	30000
Measurements	
Length (mm)	151
Height/depth (mm)	1000
Width (mm)	151
Electrotechnical data	
Voltage type	AC
Type of control gear	Not required
Nominal voltage (min) (V)	220
Protection class	I
Suitable for lamp power (min) (W)	13
Maximum system power (W)	13
Nominal voltage (max) (V)	240
Suitable for lamp power (max) (W)	13
Power factor	0.9
Luminaire efficacy (lm/W)	85