

2.3W 25000h BX

Lamp range for basic use - pure white

Airam's PRO LED 3000 K series covers all light source needs for basic use. This series includes the most common bulb types. The lamps are packed in cardboard boxes that clearly indicate the key technical specifications. Special characteristics for the lamps in this series include an extremely long operating life (25,000 h) and a high number of switch-on cycles (500,000). The colour temperature is pure white (3000 K).

Opal P45 bulb LED lamp 2.3W 3000K E14 260lm
25000h 45x78mm, cardboard packing. Supply
frequency ~50/60Hz.



2.3W 25000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713424	A7PRAJ	0.025	Pro

2.3W 25000h BX
EC001959

Mounting

Degree of protection (IP)	Other
---------------------------	-------

Structure

Colour housing	White
Energy efficiency class	E
Colour	White

Dimming and control

With remote control	No
Dimmable	No
Remote operation possible	No

Photometric data

Colour temperature (min) (K)	3000
Luminous flux (min) (lm)	260
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (max) (K)	3000
Luminous flux (max) (lm)	260
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0

Lifetime and capacity

Measurements

Length (mm)	78
Diameter (mm)	45

Electrotechnical data

Voltage type	AC
Nominal voltage (min) (V)	220
Nominal current (min) (mA)	31
Nominal voltage (max) (V)	240
Nominal current (max) (mA)	21
Power factor	0.4
Energy Efficiency Index (EEI)	0.085