

7.3W 25000h BX

Dimmable lamp range - pure white

Airam's PRO LED 3000 K dimmable series covers all basic light source needs. This series includes the most common bulb types. The lamps are packed in cardboard boxes that clearly indicate the key technical specifications. Special characteristics for the lamps in this series include an extremely long operating life (25,000 h) and a high number of switch-on cycles (500,000). The colour temperature is pure white (3000 K). The lamps in the series are dimmable by means of LED dimmers.

Opal classic dimmable LED lamp 7.3W 3000K E27
806lm 25000h 60x110mm, cardboard packing. Supply frequency ~50/60Hz.



| 7.3W 25000h BX | | | |
|----------------|--------|-------|----------------|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4713444 | A7PRBH | 0.042 | Pro Dim |

7.3W 25000h BX
EC001959

Mounting

| | |
|---------------------------|-------|
| Degree of protection (IP) | Other |
|---------------------------|-------|

Structure

| | |
|-------------------------|-------|
| Colour housing | White |
| Energy efficiency class | E |
| Colour | White |

Dimming and control

| | |
|---------------------------|-----|
| With remote control | No |
| Dimmable | Yes |
| Remote operation possible | No |

Photometric data

| | |
|--|--------------|
| Colour temperature (min) (K) | 3000 |
| Luminous flux (min) (lm) | 806 |
| Colour rendering index CRI | 80-89 |
| Colour of light acc. EN 12464-1 | Warm <3300 K |
| Colour temperature (max) (K) | 3000 |
| Luminous flux (max) (lm) | 806 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG0 |

Lifetime and capacity

Measurements

| | |
|---------------|-----|
| Length (mm) | 110 |
| Diameter (mm) | 60 |

Electrotechnical data

| | |
|-------------------------------|-------|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 |
| Nominal current (min) (mA) | 57 |
| Nominal voltage (max) (V) | 240 |
| Nominal current (max) (mA) | 53 |
| Power factor | 0.7 |
| Energy Efficiency Index (EEI) | 0.113 |