Decor 7W 15000h BX

Dimmable clear decorative lamp – warm tone

Filament lamps are suitable for replacing clear incandescent bulbs and halogen lamps. The lamps emit plenty of light towards the base. This is very important for luminaires on which the base of the lamp points downward. The lamps emit warm yellow (2200 K) light and, when combined with the elegant cord, look impressive even without a lampshade. Models that are dimmable with LED dimmers can be recognised by the DIM symbol on the package. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.

Clear classic dimmable filament LED lamp 7W 2200K E27 720lm 15000h 60x108mm, full glass, cardboard packing. Supply frequency ~50/60Hz.

7W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713731	A7GACV	0.04	Decor





7W 15000h BX

EC001959

Mounting	
Degree of protection (IP)	Other
Structure	
Colour	Other
Housing colour	Colourless
•	
Dimming and control	
Dimming phase cut-off	Yes
Dimming phase cut-on	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
The support available	110
Photometric data	
Luminous flux (min) (lm)	720
Luminous flux (max) (lm)	720
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2200
Colour temperature (max) (K)	2200
Beam angle (min)	360
Beam angle (max)	360
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1
Thotoblotogical safety according to EN 02471	1101
Lifetime and capacity	
Energine and capacity	
Measurements	
Diameter (mm)	60
Length (mm)	108
Length (mm)	100
Electrotechnical data	
	220
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	43
Nominal current (max) (mA)	43
Power factor	0.7
Voltage type	AC
Energy Efficiency Index (EEI)	0.119
Total harmonic distortion	90

