

## 7.2W 30000h BX

LED PL lamps

LED plug-in tubes are designed as a replacement for fluorescent plug-in tubes. LED tubes reach full brightness immediately, and they perform very well in cold conditions. The light does not flicker. The rated lifetime is an impressive 30,000 hours. These tubes are available in two colour temperatures: 3,000 K and 4,000 K. LED plug-in tubes with a G23 cap replace the old ESL tubes. Suitable for narrow wall luminaires, cooker hoods and under-cabinet lighting, for instance.

Opal LED plug-in tube 7.2W 3000K G23 (2-pin) 670lm 30000h 32x227.5mm, cardboard packing. Supply frequency ~50/60Hz.



7.2W 30000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713825	A7GAFT	0.042	Airam Led

7.2W 3000h BX  
EC001959

#### Mounting

Degree of protection (IP)	Other
---------------------------	-------

#### Structure

Colour	White
Colour housing	White
Energy efficiency class	F

#### Dimming and control

Dimmable	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

#### Photometric data

Luminous flux (min) (lm)	670
Luminous flux (max) (lm)	670
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Beam angle (min)	180
Beam angle (max)	180
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

#### Lifetime and capacity

##### Measurements

Diameter (mm)	32
Length (mm)	227.5

##### Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	38
Nominal current (max) (mA)	38
Power factor	0.7
Voltage type	AC
Energy Efficiency Index (EEI)	0.129