




2

12/24 V

Wardrobe rail profile Häfele Loox, Profile 5105



- > Area of application: Illuminated wardrobe rail
- > Material: Profile: Aluminium, Diffuser: Plastic
- > Internal width: 15.4 mm

Note


For LED strip lights up to a width of 10 mm.
Load bearing capacity of wardrobe rail: 20 kg/m
Note dimensions of clip connector.
LED points are always visible when this profile is used.
The surface on the aluminium profile that is to be bonded must be cleaned before bonding to the LED strip lights. It must be completely clean, grease-free and dust-free!

Supplied with

1 wardrobe rail profile
1 diffuser

Colour/finish	2500 mm
Profile: Silver coloured, Anodized	833.72.980
Diffuser: Opal white	
Packing: 1 Piece	

→ Rail centre support, for Häfele Loox wardrobe rail profile, profile 5105





- > Material: Zinc alloy
- > For wardrobe rail: Oval 30 x 15 mm
- > Installation: For screw fixing beneath shelves

Supplied with

1 rail centre support

Colour/finish	Cat. No.
Aluminium coloured, Lacquered	802.07.900
Packing: 1 Piece	

→ Rail centre support, for Häfele Loox wardrobe rail profile, profile 5105



- > Version: Height adjustable 85–105 mm
- > Material: Zinc alloy
- > For wardrobe rail: Oval 30 x 15 mm
- > Installation: For screw fixing beneath shelves



Supplied with

1 rail centre support, height adjustable

Colour/finish	Cat. No.
Aluminium coloured, Lacquered	802.07.910
Packing: 1 Piece	

DGH-M 2021, HDE-en, 10/20; Dimensional data not binding. We reserve the right to alter specifications without notice.

→ Rail end support, height adjustable, for Häfele Loox wardrobe rail profile, profile 5105




- > Version: Height adjustable (85–105 mm)
- > Material: Zinc alloy
- > For wardrobe rail: Oval 30 x 15 mm
- > Installation: For screw fixing beneath shelves

Supplied with
1 rail end support, height adjustable

Colour/finish	Cat. No.
Aluminium coloured, Lacquered	803.24.900

Packing: 1 Piece

→ Rail end support, for Häfele Loox wardrobe rail profile, profile 5105




- > Version: with 3 screw holes
- > Material: Zinc alloy
- > For wardrobe rail: Oval 30 x 15 mm
- > Installation: For screw fixing to side panel

Supplied with
1 Rail end support

Colour/finish	Cat. No.
Aluminium coloured, Lacquered	803.25.950

Packing: 1 or 50 Piece

Glass edge protection profile Häfele Loox, Profile 5108



- > For manufacturing customised glass edge lighting.
- > Effect of the glass edge on the light:
Glass edge with satin finish = even light line
Clear glass edge = point light



- > Area of application: For implementing glass edge lighting
- > Material: Profile: Plastic, Diffuser: Plastic
- > For glass thickness: 4–8 mm
- > Internal width: 15 mm
- > Installation: For plug fitting

Note

For LED strip lights up to a width of 10 mm.
Only for LED strip lights with max. 7.5 W/m.
Note dimensions of clip connector.

Without load bearing function.

The surface on the aluminium profile that is to be bonded must be cleaned before bonding to the LED strip lights. It must be completely clean, grease-free and dust-free! It is recommended to frost the rear glass edge for improved light distribution.

Supplied with
1 aluminium profile

Colour/finish	2000 mm
Profile: Silver coloured Diffuser: Milky	833.74.733

Packing: 1 Piece