

Flexible surface mounted lights


Monochrome with USB



Häfele Loox LED 2034



WITH USB CHARGING STATION



- > Dimmable: Yes
- > Version: Integrated twin USB charging station 5 V / 2 A, integrated push switch for 2 brightness levels
- > Material: Aluminium
- > Length x width: 450 x 50 mm
- > Height: 15.5 mm
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Number of LEDs: 3
- > Colour temperature: 4000 K (cool white)
- > Wattage: Max. 17 W (light: 1.5)
- > Luminous flux: 105 lm
- > Luminous efficacy: 70 (lm/W)
- > Mounting: For screw fixing beneath magnetic cover
- > Supplied with: 1 light with 2 m lead, including fixing materials

12V 5 12V Loox5 12 V driver see page 121
Please order 6-piece adapter set 833.95.753 separately.

Min. 20 W driver per light for optimum operation of the USB charging station.

4000 K	90°	
650 lx		250 mm
163 lx		500 mm
72 lx		750 mm
40 lx		1000 mm

Voltage	Colour rendering index CRI R _a	Weighted energy consumption kWh/1000 h	Finish/colour	Cat. No.
12V	82	1.65	Black	833.74.097
			Chrome plated	833.74.096