LED strip lights

RGB, 10 mm





Häfele Loox5 LED 2080/3080



LED 2080/3080

> Di > M > Fi

Dimmable: Yes
Material: Plastic
Finish/colour: White
Width: 10 mm
Height: 2.4 mm
Energy efficiency class: A+
Degree of protection: IP20

> Mounting: Self-adhesive


> Supplied with:

•

Order reference:

Please order lead separately.

Aluminium profile recommended from 9.6 W/m, see page 20



____ Cut LED strip light to length

(one contact side remains on the remainder piece; reusable)

Connect LED strip lights (two contact sides required)

C = section length

P = length of contact surface



5 12 V

Loox5 12 V driver see page 121



Loox5 24 V driver see page 122



Colour control only via 6-way distributor Häfele Connect Mesh with RGB adapter and remote control or smartphone.

Please order separately, see chapter Networking, page 96.

HAFELE

Häfele Loox5 LED 2080/3080

Volt- age	Number of	Colour tempera- ture	Wattage	Luminous flux	Luminous efficacy	Weight. energy consumpt. per m in kWh/	Section length C	Length of contact surface P	Max. strip length (visual)	Delivery length
V	LEDs/m	K	W/m	lm/m	lm/W	1000 h	mm	mm	m	5 m
5 12 V	Häfele Loox5 LED 2080									
	120	RGB	9.6	530	51	10.78	25	3.8	3.0	833.74.380
5 24 V	Häfele Loox5 LED 3080									
	120	RGB	9.6	530	51	10.78	50	3.8	6.5	833.76.386



Maximum visual strip length applies for an imperceptible drop in luminous flux of max. 30%. Maximum wattage-dependent strip length on the driver, see page 130.





> 3.5 A/20 AWG lead for LED RGB strip light, 10 mm

Voltage	Length mm	Cat. No.
5 12 V	2000	833.95.704
5 24 V	2000	833.95.710



> 3.5 A clip connector for LED RGB strip light, 10 mm

Clip connector	833.89.209



> 3.5 A/20 AWG interconnecting lead for LED RGB strip light, 10 mm

Length mm	Cat. No.
50	833.89.200
500	833.89.201
2000	833.89.202



> Corner connector, 90° rigid, 3.5 A for left or right for LED RGB strip light, 10 mm

	Cat. No.
Corner connector rigid	833.89.189