


2-way distributor with switching function Häfele Loox5


Interface for house installation with 3 control options for DALI-2™ or mains voltage push button or 1–10 V dimmer, 24 V




Control inputs (direct connection for clamping)



DALI-2™ connection diagram



Mains voltage push button connection diagram



1-10 V dimmer connection diagram

> One distributor for 3 control options: DALI-2™, power button or 1-10 V dimmer

- > Area of application: for dimming lights via DALI-2™, power button or 1-10 V dimmer.
- > Colour/finish: Black
- > Dim. (L x W x H): 149 x 50 x 16 mm
- > Switching function: on/off and dimm
- > Current carrying capacity: 5 A
- > Life time: 50,000 h
- > Installation: for glue fixing  
For screwing
- > Installation reference: Control input ports suitable for cable cross sections of 0.75–1.5 mm<sup>2</sup>

**Note**  
The memory function (for saving the dimming value after currentless) is dependent on the selected control option.

**Supplied with**  
1 distributor incl. fixing material



Input ports	Connections	Connected output ports	Control input ports	Cat. No.
1 x plug, Loox5 2-pin 24 V box to box	1 x socket, Loox5 2-pin 24 V box to box	2 x sockets, Loox5 2-pin 24 V	4 x sockets, Direct connection for clamp fixing	833.77.844

Packing: 1 or 50 Piece

**Order reference**  
The components for the switching input (DALI bus system, push button or 1-10 V dimmer) must be provided on site.  
Please order Loox5 driver 24 V separately.  
A bare ended mains lead is available for direct connection to the driver.

Häfele Loox 24 V DC driver	► MB 2.12
Alternative mains leads	► MB 2.328
Häfele Loox5 extension leads	► MB 2.301