

Concealed installation in wood,


For lead with snap-in connector Manually operated (proximity


Last state after power-off

Dimm switch (capacitive) Häfele Loox, modular

Switching function on/off by proximity sensor, dimming







- > Suitable for:
- > Switching function:
- > Memory function:
- > Material:
- > Power consumption:
- > Degree of protection:
- > Plug drill hole Ø:
- > Drill hole Ø:
- > Installation depth max.:> Installation:
- ax.: 30 mm For recessing For screwing

sensor)

Plastic

1 W

IP20

12 mm

35 mm

Installation reference:

Suitable materials: Wood, stone, glass. Do not use in metalliferous materials. Minimum distance of 500 mm to electromagnetic fields (power lines, microwave oven, etc.) must be adhered to. **The maximum installation depth for stone and glass is 10 mm.**

	IP20
Colour/finish	Cat. No.
Silver coloured	833.89.133

Packing: 1 or 50 pieces

Order reference

Please order lead with snap-in connector for modular switches separately. Length 2 m: Cat. No. 833.89.142

Sensor switch Häfele Loox, modular

Switching function Touchless soft on/off





- 8.5 -

- 40

> Switching function:

- > Memory function:
- > Material:
- > Dim. (L x W x H):
- > Power consumption:
- > Sensor range:
- > Degree of protection:
- > Installation:

On/off soft, touchless Last state after power-off Plastic 40 x 40 x 8.5 mm 0.3 W 0–80 mm IP20 For glue fixing For screw fixing

Supplied with

1 switch with fixing material

	IP20
Colour/finish	Cat. No.
Silver coloured	833.89.136
Black	833.89.180
White	833.89.181
Packing: 1 or 50 pieces	

Order reference

Please order lead with snap-in connector for modular switches separately. Length 2 m: Cat. No. 833.89.142

• Häfele Loox lead for modular switches

2

2/24 V