



2

12/24 V

Profile for recess mounting, Häfele Loox5, profile 1106



- > Material: Aluminium, diffuser: plastic
- > Internal width: 11 mm
- > Diffuser width: 11 mm
- > Routing width: 16.9 mm
- > Routing depth: 12 mm
- > Mounting: For recess mounting

Note

For LED strip lights up to a width of 5 mm. The surface of the aluminium profile must be cleaned before gluing on the LED strip lights. It must be completely clean, grease-free and dust-free!

Diffusers

Homogeneous light without points from is possible 120 LEDs/m thanks to the opal white diffuser. Points are visible with black version. If required, please order alternative diffusers in black or transparent separately.

Supplied with

- 1 aluminium profile
- 1 diffuser opal white



Length mm	Colour/finish	Light permeability	Cat. No.
2500	Profile: black, anodized, diffuser: opal white	70-80 %	833.94.107
	Profile: silver coloured, anodized, diffuser: opal white	70-80 %	833.94.106
3000	Profile: black, anodized, diffuser: opal white	70-80 %	833.95.729
	Profile: silver coloured, anodized, diffuser: opal white	70-80 %	833.95.728

Packing: 1 piece

→ End cap for Loox5 profile for recess mounting, profile 1106



- > Material: Plastic
- > Equipment: With cable outlet
- > Usable for: Häfele Loox5 installation profile, profile 1106

Supplied with

5 pairs of end caps with screws

Colour/finish	Cat. No.
Black	833.95.773
Silver coloured	833.95.772

Packing: 5 pairs

→ Diffuser, Häfele Loox for profiles for recess mounting 1106



- > Material: Plastic

Note

Homogeneous light without points from is possible 120 LEDs/m thanks to the opal white diffuser. Points are visible in the black and transparent version.

Supplied with

1 diffuser

Width mm	Colour/finish	Light permeability	2500 mm	3000 mm
11	Transparent	~90 %	833.95.807	833.95.757
11	Opal	70-80 %	833.95.805	833.95.755
11	Black	~20 %	833.95.809	833.95.759

Packing: 1 piece

TCH-F 2021, HDE-en, 10/20; Dimensional data not binding. We reserve the right to alter specifications without notice.

Profile for under mounting, Häfele Loox5, profile 2101



- > Material: Aluminium, diffuser: plastic
- > Internal width: 11 mm
- > Diffuser width: 13 mm

Note


For LED strip lights up to a width of 8 mm. The surface of the aluminium profile must be cleaned before gluing on the LED strip lights. It must be completely clean, grease-free and dust-free!

Diffusers

Homogeneous light without points from is possible 120 LEDs/m thanks to the opal white diffuser. Points are visible with black version. If required, please order alternative diffusers in black separately.

Supplied with

- 1 aluminium profile
- 1 diffuser opal white



Colour/finish	Light permeability	2500 mm	3000 mm
Profile: black, anodized, diffuser: opal white	70-80 %	833.94.111	833.95.733
Profile: stainless steel coloured, anodized, brushed, diffuser: opal white	70-80 %	833.94.112	833.95.762
Profile: silver coloured, anodized, diffuser: opal white	70-80 %	833.94.110	833.95.732

Packing: 1 piece

! Adhesive tape

► MB 2.95

→ End cap for Häfele Loox5 profile for under mounting, profile 2101



- > Material: Plastic
- > Version: With drill mark for cable outlet
- > Usable for: Häfele Loox5 profile for under mounting, profile 2101

Supplied with

5 pairs of end caps

Colour/finish	Cat. No.
Black	833.95.775
Stainless steel coloured, brushed	833.95.776
Silver coloured	833.95.774

Packing: 5 pairs

Diffuser, Häfele Loox for profile for under mounting 2101



- > Material: Plastic

Note

Homogeneous light without points from is possible 120 LEDs/m thanks to the opal white diffuser. Points are visible in the black and transparent version.

Supplied with

1 diffuser

Width mm	Colour/finish	Light permeability	2500 mm	3000 mm
13	Opal	70-80 %	833.95.806	833.95.756
13	Black	~20 %	833.95.810	833.95.760

Packing: 1 piece

TCH-F 2021, HDE-en, 10/20; Dimensional data not binding. We reserve the right to alter specifications without notice.