





## Flexglo™ F23 Vertical Bending (Silicone)



ClearTech™ TwinFlex™ C-Mask™ PinBoost™

- 5 year  
Warranty
- ANSI**  
C78.377
- 3**  
SDCM
- 55 °C  
-40 °C  
Ambient Working  
Temperature
- Anti**  
yellowing
- Mini**

Working Temp. -40~45°C / -40~113°F

Storage Temp. -40 ~ 60°C / -40~140°F

Voltage 24CV

Min. Cutting Length 83.30mm

Abmient Installation Temp. -40 ~ 50°C / -40~122°F

Max. Mounting Surface Temp. 85°C / 185°F

Power/m 9.00

Max. Running Length 7.50m

## Optical Parameters

Item Code	Finished Product						
	Color/CCT	Wavelength/CCT Tolerance	Color Tolerance	CRI	R9	Lumen/m	Lumen/ft
C-SFR-F23B-VB-24CV-40K-WM-144-80-9W-83.3	4000K	3985±150K	5SDCM	80	N/A	440.00	134.15

## Connector Type

IP67 Silicone Injection-moulded Connector

Front Connector End	Front Connector Side from Left	Front Connector Side from Right	Front Connector Bottom	Seamless Middle Connector & Power Feed	Middle Connector & Power T-feed	Jumper	End Cap
F23B-VB-SIM/FC-01/02-E-0.3m/1m/3m/5m/10m/15m/20m 22AWG*2	F23B-VB-SIM/FC-01/02-SL-0.3m/1m/3m/5m/10m/15m/20m 22AWG*2	F23B-VB-SIM/FC-01/02-SR-0.3m/1m/3m/5m/10m/15m/20m 22AWG*2	F23B-VB-SIM/FC-01/02-B-0.3m/1m/3m/5m/10m/15m/20m 22AWG*2	N/A	F23B-VB-SIM/MC-PTF-0.3m/1m/3m 22AWG*2	F23B-VB-SIM/JU-0.3m/1m 22AWG*2	F23-SIM/EC

## Mounting Profile



Serrated Aluminum Profile  
F23-SA/PL-20/500/1000/2000mm

